# PEGA RACK AND PINION INDUSTRIAL ELEVATOR

PIONEER IN INNOVATION

QUALITY - RELIABILITY - USER FRIENDLY

PEGA "PLC" PEGA "LDS" PEGA "FIS" - Programmable Landing Control for exact stop without floor ramps.

- Load Detection System for lower power consumption.
- Fault Indication System for simply fault identification.

# PEGA IL 1118 TD VFC

TECHNICAL DATA		
Payload capacity	kg	1150
Passengers		15
Speed	m/min	0-60
Lifting height	m	200
Tie spacing	m	4,5 - 15
CAR DIMENSIONS		
Internal width x length	m	1,5 x 1,8
Internal heigth	m	2,2
Door openning	m	1,43 x 2,0
ELECTRICAL DATA		
Power supply range		400V 50Hz 3Ph
Power supply fuse		50A
Power supply fuse		50A
Power supply fuse Motor machinery		50A PEGA/SEW
Power supply fuse Motor machinery Starting current		50A PEGA/SEW 34A
Power supply fuse Motor machinery Starting current Power consumption	kg	50A PEGA/SEW 34A
Power supply fuse Motor machinery Starting current Power consumption WEIGHTS	kg kg	50A PEGA/SEW 34A 20kVA
Power supply fuse Motor machinery Starting current Power consumption WEIGHTS Car weight	•	50A PEGA/SEW 34A 20kVA 1850



### GENERAL

**CONTROL SYSTEM** 

Push button control, floor call system.

The lift is equipped with frequency controlled drive and programmable control system. Different masts and tie systems to meet all kind of application demands. Car and landing doors manual with electrical and mechanical inter-locks certified/approved. Single or selective collective automatic control system, emergency lowering system. The above specification may vary based on country and region of delivery. **Norms and regulations:** EN 12159 or EN 81-1 (Directive 2006/42/EC)

## **CONSULT - SALE - SERVICE**

**PEGA HOIST Ltd.** Fáblovka 547 CZ – 533 52 Pardubice Tel.: +420 466 536 348-50 Fax.: +420 466 536 351 E-mail: info@pega-hoist.com



